

Protective

AS 930

Solvent-based, stain-proof protective treatment with gloss, wet-look effect, for antiqued marble and natural stone.



AS 930 is a solvent-based, protective stain-proofing treatment to create a gloss, wet-look effect on surfaces in marble, granite, and natural rough, cleft or antiqued stone. **AS 930** can also be used on absorbent artificial surfaces with a rough, textured finish.

The formulation of **AS 930** brings out the characteristic veins of the material to which it is applied, enhancing the natural colour and forming a shiny, ultra-hard protective layer with a characteristic wet look. It also has excellent stain-proofing properties, protects against dirt and increases resistance to foot traffic as well as notably reducing cleaning and maintenance operations.

CHARACTERISTICS AND BENEFITS

- ✓ **Brings out the characteristic veins** of the surface
- ✓ Excellent **stain-proofing properties**
- ✓ **Colour-enhancing**
- ✓ Increases surface resistance to foot traffic
- ✓ **Makes cleaning and maintenance operations much simpler**
- ✓ **Will not yellow** over time
- ✓ Creates a **highly resistant glossy protective layer**

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Marble-cement agglomerate, Slate, Sandstone, Cementine, Concrete, Cotto, Granite, Marble, Exposed brickwork, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, and Travertine.

The product can be applied on the above surfaces, with rough, antiqued or cleft finishes.

The product is **not suitable** for use on buffed, fine polished or excessively compact surfaces with low absorption

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller



FABERSURFACECARE.COM



Protective

AS 930 -Solvent-based, stain-proof protective treatment with gloss, wet-look effect, for antiqued marble and natural stone.



LINEA
PROFESSIONALE

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply AS 930 to wet or damp surfaces.
4. Apply AS 930 to surfaces with a temperature of between +5 and +40°C
5. Any adjacent surfaces not being treated with the product must be protected.

Application

6. Apply an even, light coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated and trying to treat the area in the smallest amount of time possible so that the film can cure spontaneously without any intervention on areas already completed.
7. If there are any differences in shine during the drying stages, due to the different degree of absorption on the surface, do not try to even out the product; wait for it to cure completely (about 4-6 hours) and then repeat the application following the same process as described above, trying to even out the appearance of the surface.

Drying time

The product is fast drying and in any case, within 45 minutes from application.

Opening to floor traffic

The surface can be opened to floor traffic about 4-6 hours after the product has been applied.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For *routine cleaning* of a surface treated with AS 930, we recommend: NEUGEL
- For *routine cleaning* of a surface treated with AS 930, we recommend: NEUGEL
- For *de-waxing* a surface treated with AS 930, we recommend: DEC 21 and/or DECERA P

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces, or shiny or dirty surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high-penetrant water repellent, wait for this to dry completely before applying AS 930
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in presence of mist, fog or high levels of humidity.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- After applying a layer of AS 930, leave to cure without re-touching or intervening in the treated area before it is completely dry; this is to prevent uneven finishes after drying.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.



Protective

AS 930 -Solvent-based, stain-proof protective treatment with gloss, wet-look effect, for antiqued marble and natural stone.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION

Aspect	: Liquid
Color	: Transparent
Odour	: Solvent Acetate
Specific gravity (20°C)	: 930 ± 10 g/Lt.
Flash point (ASTM D 56)	: N.R.

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION



H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P501	Dispose of contents/container to special or dangerous waste points



LINEA
PROFESSIONALE

Protective

AS 930 -Solvent-based, stain-proof protective treatment with gloss, wet-look effect, for antiqued marble and natural stone.



Version 2.0 – 11/07/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

FABERSURFACECARE.COM

