



SHOWROOM LINE



Cleaners

ALKALINE CLEANER

Alkaline cleaner to strip wax and remove deep grease stains, oxidation, and suction cup marks

ALKALINE CLEANER is a water-based, alkaline cleaner for the deep cleaning of greasy dirt and to remove organic residues, dark marks, and oxidation, as well as to strip wax or old layers of wax or existing treatments.

ALKALINE CLEANER can be used in combination with the SOLVENT STRIPPER for even deeper cleaning to carry out "double wax stripping".

ALKALINE CLEANER can be used to remove suction cup marks from ceramic surfaces, caused by processing and handling in industrial production environments.

BENEFITS

- ✓ Concentrated Formula
- ✓ Effective against greasy dirt and old treatments
- ✓ Versatile
- ✓ High cleaning power

USES

Suitable for indoor and outdoor applications.

Suitable for marble-resin agglomerates, marble-cement agglomerates, quartz-resin agglomerates, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete tiles, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Bricks, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

White Pad, Single disk machine

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Wait for the surface to be treated to be completely dry.
- Any surfaces close by not to be treated with the product must be protected.
- Apply the product to surfaces with a temperature between +5 and +40°C

Application

- Dilute the product in clean water. Pour 1 part product into 4 parts water. If used to remove the suction cup mark, dilute 1 part of the product in 1 part of water (50%), or use undiluted for stronger removing action.
- Begin to work the product over the surface, rubbing the surface with the tool of choice.
- Let the product act for 5 - 10 minutes, working it every now and then to boost its action.

MADE IN ITALY

100%



SHOWROOM LINE

APPLICATION
STEPS

- Once the time has passed, remove all residues and rinse the whole floor with plenty of water. If the result is only partially achieved, repeat the application process following the same steps and if necessary, slightly increase the concentration of the product in water.

Resume Surface Use

- After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

APPLICATION
STEPS
DOUBLE WAX
STRIPPING

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Wait for the surface to be treated to be completely dry.
- Any surfaces close by not to be treated with the product must be protected.
- Apply the product to surfaces with a temperature between +5 and +40°C

SOLVENT
STRIPPER +
ALKALINE
CLEANER*Application*

- Pour **SOLVENT STRIPPER** undiluted, straight onto the surface being treated.
- Begin to work the product over the surface, rubbing the surface with the tool of your choice.
- Let the product act for 5 - 10 minutes, working it every now and then to boost its action.
- Once the indicated time has passed, without removing any residues pour **ALKALINE CLEANER** directly on the surface following the previously described procedure.
- Work **ALKALINE CLEANER** with a white pad and a single disk machine.
- Once the operations are over remove the residues and then rinse the surface with plenty of clean water.

Resume Surface Use

After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

COMPLEMENTARY
MAINTENANCE
PRODUCTS
MANUTENZIONE

After cleaning with **ALKALINE CLEANER** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

INSTRUCTIONS
AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use in combination with other chemicals if not specifically required
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM



SHOWROOM LINE

**EQUIPMENT CLEANING**

The equipment used can be cleaned with water

PHYSICAL AND TECHNICAL DATA

| | |
|--------------------------|---------------|
| Formula | Clear Liquid |
| Color | Amber |
| Odor | Tipycal |
| pH | 13 ± 0,5 |
| Specific gravity at 20°C | 1120 ± 10 g/l |

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles - 12 bottles per box
5 l bottles - 4 bottles per box
10 l tanks

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev4.0 – 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM