



SHOWROOM LINE



## Cleaners

# WAX REMOVER

**Alkaline-based wax stripper for deep removal of greasy dirt, old treatments, and existing layers of wax.**

**WAX REMOVER** is an alkaline-based wax stripper for the removal of organic dirt, greasy surface stains, and greasy dirt, even if stubborn or old. It is also effective on mold, and algae. It can also be used to remove existing surface treatments and old layers of wax.

**WAX REMOVER** can be used in combination with the **SOLVENT STRIPPER** for even deeper cleaning to perform the “double wax stripping”.

### BENEFITS

- ✓ Great cleaning power against old treatments and waxes
- ✓ Effective against greasy dirt
- ✓ Versatile
- ✓ High cleaning power

### USES

**Suitable** for indoor and outdoor applications.

**Suitable** for marble-resin agglomerates, marble-cement agglomerates, quartz-resin agglomerates, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete tiles, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Bricks, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quartzite, Terracotta, Travertine, Tuff

### COVERAGE

10/15 m<sup>2</sup>/l

### APPLICATION EQUIPMENT

White Pad, Single disk machine

### APPLICATION STEPS

*Before applying the product it is necessary to take a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material*

#### *Surface Preparation*

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Protect any surface close by that is not meant to be treated.
- Apply the product to a dry surface with a temperature between +5 e +40°C
- Wait at least 2 days after the installation for the grouting to cure completely

#### *Application*

- Dilute the product in clean water. Pour 1 part of the product into 4 parts of water. If used to remove the suction cup mark, dilute 1 part of the product in 1 part of water.
- Begin to work the product over the surface, rubbing the surface with the preferred tool.
- Let the product act for 5 - 10 minutes, working it every now and then to boost its action.
- Once the time has passed, remove all residues and rinse the whole floor with plenty of water. If the result is only partially achieved, repeat the application process following the same steps and if necessary, slightly increase the concentration of the product in water.

MADE IN ITALY

100%



## SHOWROOM LINE

APPLICATION  
STEPS*Resume surface use*

- After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

APPLICATION  
STEPS  
DOUBLE WAX  
STRIPPING

*Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material*

SOLVENT  
STRIPPER + WAX  
REMOVER*Surface Preparation*

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Wait for the surface to be treated to be completely dry.
- Any surfaces close by not to be treated with the product must be protected.
- Apply the product to surfaces with a temperature between +5 and +40°C

*Applicazione*

- Pour **SOLVENT STRIPPER** undiluted, straight onto the surface being treated.
- Begin to work the product over the surface, rubbing the surface with the tool of your choice.
- Let the product act for 5 - 10 minutes, working it every now and then to boost its action.
- Once the indicated time has passed, without removing any residues pour **WAX REMOVER** directly on the surface following the previously described procedure.
- Work **WAX REMOVER** with a white pad and a single disk machine.
- Once the operations are over remove the residues and then rinse the surface with plenty of clean water.

*Resume Surface Use*

After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.

COMPLEMENTARY  
MAINTENANCE  
PRODUCTS  
MANUTENZIONE

After cleaning with **WAX REMOVER** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

INSTRUCTIONS  
AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use in combination with other chemicals if not specifically required
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT  
CLEANING

The equipment used can be cleaned with water

MADE IN ITALY

100%



## SHOWROOM LINE

**PHYSICAL AND TECHNICAL DATA**

Formula	Liquid
Color	Amber
Odor	Tipycal
pH	12 ± 0,5
Specific gravity at 20°C	1030 ± 10 g/l

**STORAGE** Keep the container tightly closed and store in a cool, dry place.

**SHELF LIFE** 36 months in the original, sealed packaging, stored in a cool, dry place.

**PACKAGING** 1 l bottles - 12 bottles per box  
5 l bottles - 4 bottles per box

**ACCIDENTAL SPILLS** Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

**SAFETY** When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev6.0 – 12/09/2022

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*

MADE IN ITALY

100%