





Finishing Products

MAINTENANCE WAX

Wax for the maintenance and restoration of the waxed surface

MAINTENANCE WAX is a water-based wax for the maintenance and restoration of waxed surfaces. The formulation of **MAINTENANCE WAX** has been developed to be compatible with water-based waxes of all kinds and can therefore be used independently of the type of wax used beforehand.

BENEFITS

- ✓ It brings out the shine of the material
- ✓ Effective against dirt and staining agents
- ✓ It doesn't yellow overtime
- ✓ Good resistance to foot traffic

USES

Suitable for indoor application.

The product is **suitable** to be applied on surfaces previously treated with water-based waxes.

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Lambswool applicator

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material.

Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply MAINTENANCE WAX to wet or damp surfaces.
- Apply MAINTENANCE WAX to surfaces with a temperature between +5 and +40°C
- Any surfaces close by not being treated with the product must be protected.

The product is used diluted in clean water, according to the type of surface to be restored and the condition of the pre-existing wax layer.

Maintenance (regular treatment of a wax layer in good condition and with no specific signs of wear):

- For compact and non-absorbent surfaces, such as textured stoneware and ceramics, marble, granite, and natural stone with semi-polished finish and parquet, dilute 1 part of the product in 9 parts of water;
- For textured, absorbent surfaces, such as cotto, terracotta, natural wood, marble, granite, and tumbled natural stone with sanded or textured finish, dilute it 1 part product in 4 parts water.

Restoration (treatment of a worn wax layer with signs of wear, scratches, abrasions, discolouring and obvious aesthetic differences):

- For compact and non-absorbent surfaces, such as textured stoneware and ceramics, marble, granite, and natural stone with semi-polished finish and parquet, dilute 1 part of product in 4 parts of water;
- For textured, absorbent surfaces, such as cotto, terracotta, natural wood, marble, granite, and tumbled natural stone with sanded or textured finish, dilute 2 parts of product in 5 parts of water;



SHOWROOM LINE



APPLICATION STEPS

Application

- The application of MAINTENANCE WAX requires a wash and wax technique: apply a thin, even coat of the diluted solution to a clean, dry surface using a mop, squeezed out so that it leaves an even layer of product without creating excessive build up. Make sure to create an even layer to cover the whole surface being treated.
- In case of particularly absorbent or rough surfaces, for a greater coverage or restoration effect, it is possible to apply a second coat around 2-3 hours from the first.
- MAINTENANCE WAX is a self-polishing wax that once applied, will create an extremely polished effect. In the event you wish to increase the surface shine, it is possible to do so using a traditional mechanical floor polisher with white or lambswool pad. Wait a minimum of 3-4 hours for the wax to cure and then clean the surface dry, polishing until the required surface shine is achieved. Using a mechanical polisher also makes it possible to clean up any flaws created by a build-up of product in a specific surface area, in case of application of two coats of product.

Resume Surface Use

The product is fast drying and in any case, no more than 1-2 hours from application. The surface can be opened to floor traffic about 4-6 hours after the product has been applied.

COMPLEMENTARY MAINTENANCE PRODUCTS

To maintain a surface treated with MAINTENANCE WAX use the most suitable Faber cleaner, such as NEUTRAL CLEANER o FLOOR CLEANER, depending on the nature of the surface. To maintain the wax layer use MAINTENANCE WAX following the previously described procedure.

INSTRUCTION AND GUIDELINES

- Never apply the product to wet, damp or overheated surfaces.
- Do not apply the product to acid-treated surfaces.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use on outdoor surfaces.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment can be cleaned with water.

PHYSICAL TECHNICAL DATA

	·
Formula	Liquid
Color	White
Odor	Typical
рН	8.0 ± 0.5
Specific Gravity at 20°C	1100 ± 10 g/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 1 I bottles - 12 bottles per box

5 I bottles - 4 bottles per box



SHOWROOM LINE



ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev 3.0 - 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.