



SHOWROOM LINE



Finishing Products

GRES & STONE WAX

Protective matt-finish wax for floors made of bricks, natural stone concrete or textured stoneware

GRES & STONE WAX is a water-based self-polishing wax for floor surfaces made of natural stone, bricks, concrete, natural wood, parquet, and textured ceramic tiles.

GRES & STONE WAX adds a satin finish to the floor on which it is applied and lightly enhances the original color of the material. The product provides water- and oil-repellent features. The product also seals the textures of the surface, making daily cleaning and maintenance operations much easier.

BENEFITS

- ✓ It enhances the color of the material
- ✓ It protects against staining agents and dirt
- ✓ It provides a satin finish
- ✓ It doesn't yellow overtime
- ✓ It protects against foot traffic

USES

Product **suitable for** indoor use.
Suitable for use on Marble-cement agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Concrete Tiles, Concrete, Clinker, Cotto, Granite, Natural porcelain tiles, Textured porcelain tiles, Wood, Limestone, Marble, Parquet or natural wood, Quartzite, Terracotta, Travertine, Tuff.

COVERAGE

20/30 m²/l

APPLICATION EQUIPMENT

Lambswool applicator

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material.

Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Wait for the surface to be completely dry.
- Any surface in the premises not being treated must be protected.
- Apply the product on surfaces with a temperature within this range +5 | +40°C

When applying it to medium-high-absorbing surfaces, we strongly recommend first applying a water-repellent product to act deep down and allow the **GRES & STONE WAX** to catalyze correctly on the surface of the material.

When applying to compact, non-absorbent surfaces such as quartz, ceramic or porcelain tiles, dilute the product in water, with a 1:1 ratio.

Application

- Apply an even, abundant coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated. We recommend always following the same application direction and pattern.

MADE IN ITALY

100%



SHOWROOM LINE



APPLICATION STEPS

- Take care not to leave too much product when applying the wax and if you notice any areas of product build-up, proceed to redistribute it while working on that section.
- If, while applying the wax, you should notice any build-up in an area where the product has already been applied, do not attempt to even out the layer of material: wait for the first layer to cure and then intervene, as described later.
- In case of application on particularly absorbent or textured surfaces, it may be necessary to add a second coat of product. Only apply a second coat once the first is perfectly dry. Wait 2-3 hours between coats. We recommend applying the second coat in a direction that crosses the first one.
- **GRES & STONE WAX** is a self-polishing wax that once applied, will create an extreme satin effect. In the event you wish to increase the surface shine, it is possible to do so using a traditional mechanical floor polisher with white or lambswool pad. Wait a minimum of 3-4 hours for the wax to cure and then clean the surface dry, polishing until the required surface shine is achieved. Using a mechanical polisher also makes it possible to clean up any flaws created by a build-up of product in a specific surface area, in case of application of two coats of product.

Resume Surface Use

The surface can be opened to floor traffic about 4-6 hours after the product has been applied.

COMPLEMENTARY MAINTENANCE PRODUCTS

To maintain a surface treated with **GRES & STONE WAX** use the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface. To maintain the wax layer use **MAINTENANCE WAX** or **GRES & STONE WAX** diluted 1:5.

INSTRUCTION AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not apply the product on outdoor surfaces
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT CLEANING

At the end of the application the equipment can be cleaned with water.

PHYSICAL TECHNICAL DATA

Formula	Liquid
Color	White
Odor	Typical
pH	8,0 ± 0,5
Specific Gravity at 20°C	1020 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles - 12 bottles per box
5 l bottles - 4 bottles per box

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM



SHOWROOM LINE



ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev. 3.0 – 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%