SHOWROOM LINE



Honing and Polishing

SHINE REPAIR LIGHT

Polishing cream that reduces defects, dullness, light scratches, and dirt sensitivity from light-toned glazed polished porcelain ceramic tiles

SHINE REPAIR LIGHT is a water-based cream product to be used on light-toned glazed polished and full-body polished porcelain ceramic tile to minimize scratches and defects.

SHINE REPAIR LIGHT allows to Increase the sheen on dull areas of the surface and to restore or reduce the visibility of scratches.

BENEFITS

- Specific for light-toned glazed polished porcelain tiles
- ✓ It enhances the surface resistance against dirt.
- ✓ It increases the shine of the surface
- ✓ It minimizes scratches, abrasions and surface dullness

USES

Suitable for indoor and outdoor applications.

Suitable for light-toned glazed polished ceramic tiles, light-toned full-body polished ceramic tiles

COVERAGE

NA

APPLICATION EQUIPMENT

White pad, single disk machine, hand polisher

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner. If the surface is particularly dirty we recommend cleaning it with DEEP DEGREASER
- Wait for the surface to be treated to be completely dry.
- Any surfaces close by not to be treated with the product must be protected.
- Apply the product to surfaces with a temperature between +5 and +40°C

Applicazione

- Shake the bottle for about 30 seconds before use, and pour a few drops on the area to be treated.
- Start to work the product in circular motions using the white pad, making sure to treat the whole surface evenly.
- Work the product using a white pad in circular motions applying some pressure on the pad.
- Keep working the product on the surface until completely dry. At the end of the application evaluate the achieved result, if necessary apply the product again. Depending on the case up to 10 applications can be performed.
- Once the job is done remove the residues and rinse with water

Resume Surface Use

After carefully removing any residues and rinsing the surface with water, the floor can be opened to foot traffic.



SHOWROOM LINE



COMPLEMENTARY
MAINTENANCE
PRODUCTS
MANUTENZIONE

After using SHINE REPAIR LIGHT keep the surface clean using FLOOR CLEANER.

INSTRUCTIONS AND GUIDELINES

- Do not apply the product on surfaces that are not fully clean
- Do not apply the product on wet or heated surfaces
- Do not apply the product on matt or natural porcelain tiles
- Do not apply the product on surfaces that aren't light-toned
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT CLEANING

The equipment used can be cleaned with water

PHYSICAL AND TECHNICAL DATA

Formula	Cream
Color	White
Odor	N.A
pH	10 ± 0.5
Specific gravity at 20°C	N.A

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 250 MI bottles - 12 bottles per box

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY When applying the product, always use suitable personal protective equipment

and follow the instructions on the product safety data sheet with care.

Rev1.0 - 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.