



SHOWROOM LINE



Protective Treatments

COLOUR ENHANCER MATT FINISH

Color-enhancing, stain-proof impregnator with a matt finish, for all absorbing surfaces

COLOUR ENHANCER MATT FINISH is a solvent-based, color-enhancing stain-proof impregnating treatment that penetrates the surface without creating a film. It provides a matt finish and is suitable for all medium and medium-high absorbing materials with a non-polished finish.

COLOUR ENHANCER MATT FINISH also makes surface maintenance easier, as it limits a surface's ability to trap dirt, preventing dirt and stains from penetrating the material.

BENEFITS

- ✓ Stain-proof protection
- ✓ UV resistant
- ✓ It won't yellow overtime
- ✓ It reduces the ability of the surface to trap dirt
- ✓ Certified safe for use on surfaces in contact with food

USES

Suitable for indoor and outdoor applications.

Suitable for Marble-resin agglomerates, Quartz-resin agglomerates, Slate, Sandstone, Basaltina - Lava rock, Molten basalt, Concrete tiles, Concrete, Cotto, Granite, Limestone, Marble, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, Travertine, and Tuff.

COVERAGE

10-15 m²/l according to the absorption level of the surface being treated

APPLICATION EQUIPMENT

Brush, roller, lambswool applicator, airless spray, cloth

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Wait for the surface to be treated to be completely dry.
- All surfaces close by not being treated must be protected
- Apply the product on surfaces with a temperature between +5 e +40°C

Application

- Apply an even layer of product to cover the whole surface being treated, using the preferred tool. Make sure to create a layer that is as seamless and even as possible.
- After about 10 minutes from the application, make sure that there are no residues or excess product on the surface, and redistribute them if necessary, until they are completely absorbed.
- When applying the product to more absorbing surfaces, apply a second coat about 1-2 hours after the first one, following the same procedure described above.
- Once the treatment is done wait 24 hours before washing the surface. Wait up to 48 hours to allow the product to settle even more into the material for a long lasting performance.

MADE IN ITALY

100%



SHOWROOM LINE

**APPLICATION STEPS***Resume surface use*

Surfaces will be dry about 1 hour from product application. When used on floor surfaces, wait at least 6 hours before opening the floor to foot traffic.

COMPLEMENTARY MAINTENANCE PRODUCTS MANUTENZIONE

After the treatment with **COLOUR ENHANCER MATT FINISH** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

INSTRUCTIONS AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- When used after a water-repellent sealer it is necessary to wait for the treatment to be completely dry before proceeding with **COLOUR ENHANCER MATT FINISH**
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT CLEANING

The equipment used can be cleaned with white spirit

PHYSICAL TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Solvent
Flammability (ASTM D56)	30 °C open vase
Specific gravity 20°C	800 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles - 12 bottles per box
5 l bottles - 4 bottles per box

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev4.0 – 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.