



SHOWROOM LINE



## Protective Treatments

# STONE COLOUR ENHANCER

**Color-enhancing, stain-proof impregnator with a semi-polished wet-look finish, for all absorbent surfaces.**

**STONE COLOUR ENHANCER** is a solvent-based, color-enhancing, and stain-proof impregnating treatment that penetrates the surface, leaving a semi-polished finish and ensures great protection against staining agents to all medium-absorbing materials that are not polished.

**STONE COLOUR ENHANCER** makes surface maintenance easier, as it limits the surface's ability to trap dirt, preventing dirt and stains from penetrating the surface..

### BENEFITS

- ✓ Great stain-proof performance
- ✓ UV resistant
- ✓ It won't yellow overtime
- ✓ It reduces the ability of the surface to store dirt
- ✓ It enhances the color of the material

### USES

**Suitable** for indoor and outdoor applications.

**Suitable** for Cement-marble agglomerates, Slate, Sandstone, Basaltina - Lava rock, Cementine, Cotto, Granite, Limestone, Marble, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, Travertine, and Tuff

### COVERAGE

10-15 m<sup>2</sup>/l according to the absorption level of the surface being treated

### APPLICATION EQUIPMENT

Brush, roller, lambswool applicator, airless spray, cloth

### APPLICATION STEPS

*Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material*

#### Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Wait for the surface to be treated to be completely dry.
- All surfaces close by not being treated must be protected
- Apply the product on surfaces with a temperature between +5 e +40°C

#### Applicazione

- Apply an even layer of product to cover the whole surface being treated, using the preferred tool. Make sure to create a layer that is as seamless and even as possible.
- After about 10 minutes from the application, make sure that there are no residues or excess product on the surface, and redistribute them if necessary, until they are completely absorbed.
- When applying the product to more absorbing surfaces, apply a second coat about 1-2 hours after the first one, following the same procedure described above.
- Once the treatment is done wait 24 hours before washing the surface. Wait up to 48 hours to allow the product to settle even more into the material for a long lasting performance.

MADE IN ITALY

100%



## SHOWROOM LINE

**APPLICATION STEPS***Resume surface use*

Surfaces will be dry about 1 hour from product application. When used on floor surfaces, wait at least 6 hours before opening the floor to foot traffic.

**COMPLEMENTARY MAINTENANCE PRODUCTS MANUTENZIONE**

After the treatment with **STONE COLOUR ENHANCER** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

**INDICAZIONI E RACCOMANDAZIONI**

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- When used after a water-repellent sealer it is necessary to wait for the treatment to be completely dry before proceeding with **STONE COLOUR ENHANCER**
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

**EQUIPMENT CLEANING**

The equipment used can be cleaned with white spirit

**PHYSICAL TECHNICAL DATA**

Formula	Liquid
Color	Clear
Odor	Solvent
Flammability (ASTM D56)	<21°C
Specific gravity 20°C	840 ± 10 g/l

**STORAGE**

Keep the container tightly closed and store in a cool, dry place.

**SHELF LIFE**

12 months in the original, sealed packaging, stored in a cool, dry place.

**PACKAGING**

1 l bottles - 12 bottles per box  
5 l bottles - 4 bottles per box

**ACCIDENTAL SPILLS**

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev8.0 – 12/09/2022

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*