

# LIQUID WAX

Liquid wax polish and restoration treatment for marble, granite and natural stone surfaces



LINEA PROFESSIONALE

**LIQUID WAX** is a fast-drying, solvent-based liquid wax to polish and restore natural stone surfaces. Its formula features a careful balance of ingredients for quick and easy application, even on irregular surfaces, such as stair risers, statues, tops and furnishing items in general, where the use of other polishes would be labour-intensive or difficult.

**LIQUID WAX** provides an excellent shine and at the same time, restores the tone, colour and aesthetic features of the material treated. **LIQUID WAX** also stands out for its quick, easy application, thanks to its fast-drying action. A surface treated with **LIQUID WAX** is also protected against water and stain penetration, thanks to its water- and oil-repellence, which also make successive cleaning and maintenance operations easier.

## CHARACTERISTICS AND BENEFITS

- ✓ **Brings out the shine** on the treated material
- ✓ **Quick and easy application**
- ✓ **Increases surface shine**
- ✓ Leaves the surface with excellent **water repellence**
- ✓ **Makes surface maintenance easier**
- ✓ **Will not yellow** over time
- ✓ **Fast drying**
- ✓ **Effective stain protection**

## USES

Product **suitable** for indoor and outdoor use.

**Suitable** for use on: Marble-cement agglomerate, Slate, Basaltina - Lava stone, Cementina, Clinker, Cotto, Granite, Limestone, Marble, Quartzite, Terracotta, Travertine

## COVERAGE

15/25 m<sup>2</sup>/l

## APPLICATION EQUIPMENT

### **Product application:**

Brush, Lambswool applicator, Cloth

### **Product polishing**

Orbital or flexible polisher, arm polishing machine,



## Waxes and Finishes

**LIQUID WAX** *Liquid wax polish and restoration treatment for marble, granite and natural stone surfaces*



### APPLICATION STEPS

#### Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply LIQUID WAX to wet or damp surfaces.
3. To boost product penetration, we recommend warming the surface being treated.
4. Any adjacent surfaces not being treated with the product must be protected.

#### Application

5. Apply an even coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface area.

6. 5-10 minutes later but in any case on the completely dry layer of the product, proceed to polish the surface. This operation can be carried out manually on small surfaces, using a wool-cotton cloth, white or wire wool pad. In case of larger areas, we recommend using a tool such as the orbital or flexible polisher or arm polishing machine, complete with white, felt or lambskin pad, or wire wool. Work the surface, brushing or polishing until all excess has been removed and the end result is both even and polished.

#### Drying time

The product is fast drying and in any case, no more than 5-10 hours from application.

### COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For de-waxing a surface treated with LIQUID WAX, we recommend: DEC 21 and/or DECERA P

### INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

### EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

### SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

### STORAGE

Keep the container tightly closed and store in a cool, dry place.

### SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

### PACKAGING

- 1 l bottles - 12 bottles per box



## Waxes and Finishes

**LIQUID WAX** Liquid wax polish and restoration treatment  
for marble, granite and natural stone surfaces



LINEA  
PROFESSIONALE

### DATI FISICO-TECNICI

Aspect:	Paste-like emulsion
Colour:	Matt or colorless (depending on storage temperature)
Odour:	Solvent
Specific Gravity at 20°C	1540 ± 20 g/l
Flash Point (ASTM D 56)	N.R.

### HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer .
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

Version 3.0 – 21/03/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

*The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.*

